



光缆示意图  
Optical cable Diagram

A端/Side A



×6

B端/Side B



×6



6*12CMPO-6*12CMPO Type:B Fiber Connectivity												
Side/A1 MPO	P1	P2	P3	P4	P5	P6	P7		P9	P10	P11	P12
Fiber Colour	BL	OR	GR	BR	GR	WH	RE		YE	PU	PI	AQ
Side/B1 MPO	P12	P11	P10	P9	P8	P7	P6		P4	P3	P2	P1
Side/A6 MPO	P1	P2	P3	P4	P5	P6	P7		P9	P10	P11	P12
Fiber Colour	BL	OR	GR	BR	GR	WH	RE		YE	PU	PI	AQ
Side/B6 MPO	P12	P11	P10	P9	P8	P7	P6		P4	P3	P2	P1

光缆参数 Cable Parameters		
光纤芯数 Fiber Core		72C
光纤规格 Fiber Type		MM/OM3-50/125um
工作温度 Operating Temperature		-40~70℃
衰减 Attenuation		≤2.3dB/km@850nm
外护套 Outer Jacket	外径 Dimension	11.2mm
	材料 Material	LSZH
	颜色 Color	青绿/Aqua
拉力 Tension	短期 Short term	300N
	长期 Long term	150N

连接器参数 Connector Parameters		
连接器型号/Connector Type		MPO/UPC/F/OM3/12C
标损 Elite Loss		≤0.75dB
低损 Standard Loss		≤0.35dB
回损 Return Loss		≥30dB
基准波段 Tesr Wavelength		@850nm
可重复性 Repeatability		≤0.2dB
互换性 Interchangeability		≤0.2dB
插拔次数 Durability		800~1000
工作温度 Operating Temperature		-40~75℃