



光缆示意图

Optical cable Diagram

A端/Side A

B端/Side B



×4

×4



4*12 CMPO-4*12 CMPO Type:A Fiber Connectivity													
Side/A1	MPO	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12
Fiber Colour		BL	OR	GR	BR	GR	WH	RE		YE	PU	PI	AQ
Side/B1	MPO	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12
Side/A4	MPO	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12
Fiber Colour		BL	OR	GR	BR	GR	WH	RE		YE	PU	PI	AQ
Side/B4	MPO	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12

光缆参数 Cable Parameters

连接器参数 Connector Parameters

光纤芯数 Fiber Core	48C	
光纤规格 Fiber Type	MM/OM3-50/125um	
工作温度 Operating Temperature	-40~70℃	
衰减 Attenuation	≤2.3dB/km@850nm	
外护套 Outer Jacket	外径 Dimension	9.0mm
	材料 Material	LSZH
	颜色 Color	青绿/Aqua
拉力 Tension	短期 Short term	300N
	长期 Long term	150N

连接器型号/Connector Type	MPO/UPC/F/OM3/12C
标损 Elite Loss	≤0.75dB
低损 Standard Loss	≤0.35dB
回损 Return Loss	≥30dB
基准波段 Tesr Wavelength	@850nm
可重复性 Repeatability	≤0.2dB
互换性 Interchangeability	≤0.2dB
插拔次数 Durability	800~1000
工作温度 Operating Temperature	-40~75℃